

KCS C-2700 STEREO AMPLIFIER



KELONIK CINEMA SOUND



Stereo Amplifier

The KCS C-2700 is the perfect equipment to amplify Low frequencies on most of screen speakers setup. With the parallel mode you are also able to amplify several Surround speakers with enough power.

Efficient heat sink, variable speed cooling fan, ensures the amplifier working at low temperature.

Large annular transformer ensures enough power supply.

Perfect protection, including limit, on/off shock protection, DC protection, output short circuit protection and overheat protection.

In-built limiter it is a very effective protection against electrical damage to the speaker.

Stereo, Bridge and Parallel working mode.

Each channel has its own Signal and Clip indicator.

When the protection circuit works, fault indicator lights and sound output automatically stop at the same time.

Front panel level gain control.

The newest SMD component technology makes the product more stable and reliable.

KCS C-2700 STEREO AMPLIFIER

TECHNICAL DATA



Rated power / Model	KCS C-2700
1 kHz (HIA) with 0,5% THD	
4 Ω per channel)	2 x 1.350 W
8 Ω (per channel)	2 x 1.000 W
8 Ω Bridge (mono)	2700 W
Performance	
Frequency Response (@ 1W)	20Hz - 20KHz, +0-1dB
Total Harmonic Distorsion (THD)	<0,5%, 20Hz-20KHz
Intermodulation Distorsion 60 Hz and 7 KHz at 4:1 from full rated output to -30 dB	=/<0,35%
Slew Rate	>10 V us
Voltage Gain	36dB
Damping Factor (8 Ω) 10Hz-400 Hz	>200
Signal to noise ratio (below rated power, 20Hz to 20KHz. A-weighted)	>100 dB
Crosstalk (below rated power)	
@1 KHz	-75 dB
@20 KHz	-58 dB
Input sensitivity for full rated power	
@ 8 Ω	0,775 V or 1,4 V
Input impedance (nominal)	
balanced	20 K Ω
Unbalanced	10 K Ω
Construction	
Dimensions (W x D x H)	482 x 294 x 88 mm
Net Weight	19,5 kg
4R/ 1 /8 Consumption	500 W - 3,1 A

Protection Protection against Short circuits, no-load, on/off muting, RF interference
Ventilation Flow-through ventilation from front to back
Cooling Internal heat sinks with forced aor. Fan cooled, speed regulated, thermal protection
Power cable specification Plug: 10A, 250 V - Wire: 3x1,0 mm²